



Forklift Camera Solutions (Non-Ex Proof)

Model No. SE-01-001



Product Description:

An ideal solution for forklift operators, the Forklift camera system comes equipped with Four - Rugged Design cameras, a LCD screen, MDVR with recording capability and complete wiring. The system ensures safe transportation with increased pedestrian safety and blind spot elimination.

Forklift Wired Camera

Model No. SE-01-001/C



Product Features:

- ☐ NVP2431H + 1/3" CMOS AR0130 image sensor
- ☐ Metal-cased mini housing with standard fixed lens.
- ☐ Easy installation
- ☐ Support 12V DC $\pm 10\%$, Low power consumption.
- ☐ IP67 Waterproof & Vandalproof, 3.6mm / 2.8mm lens optional
- ☐ Support IR function, infrared LED range 10m





Product Specifications:

Image Sensor	1/3"COMS
Horizontal Resolution	2.0 Megapixel
TV System	PAL/NTSC
Effective Pixel	1920*1080
Minimum Illumination	Color 0.01Lux;IR ON 0 Lux
S/N Ratio	≥69dB (AGC OFF)
Day/Night mode	ICR IR filter automatically switches
Auto Gain Control	AUTO
Backlight compensation	AUTO
White Balance	AUTO
Noise Reduction	2D/3D
WDR	Digital WDR
Lens	2.8mm Megapixel Lens , M12*P0.5 Port
Electronic Shutter	AUTO/1/50 (1/60) -1 (100, 000Sec)
Video Output	AHD VIDEO(960P)
IR Leds Qty	18 Pcs & 5 Leds
IR Distance	10-15 Meters
Waterproof Grade	IP66
Operating Temp.	-20°C~+70°C
Power Supply	DC12V±10%
Power Consumption	≤4W
Size	101*69*7

Wired Monitor 7"

Model No. SE-01-001/M



Product Specifications:

LCD	7" high gloss digital screen / 16:9
Resolution/brightness/viewing Angle (standard)	1024*600, LED 350- 400 CD/m ² , left and right - 70°, top -50°, bottom - 70°
CVBS input	Two video inputs, one reversing trigger V2
Special features	Light sensor function, automatic screen brightness adjustment for day and night, reversing delay, reversing scale
System	PAL / NTSC
OSD control	Brightness, contrast, colour, multi-language, mirroring, reverse delay
Power Requirements	Input 9-36V DC, output 12V
Other	High and low voltage protection and anti-phase protection, anti-shock pulse 60V 3A
Power Consumption	<5W
Waterproof/ dustproof rating	IP69K
Seismic rating	5.9G
Operating temperature	-20°C +70°C
Storage temperature	-30°C to 80°C
Wire interface	4PIN airline header with RCA female connector (optional)
External dimentions	188*127.2*34(79)mm
Exterior colours	Matt black all metal
Annexes	Remote control, power cord, user manual hardware U-bracket, removable sun visor

Mobile DVR

Model No. SE-01-001/D





Product Specifications:

Video	Video Input	Supports 4 channels CIF/HD1/D1/960H camera Video input Supports 4 channels 720P AHD camera Video input Supports 4 channels 1080P AHD camera Video input Supports 2-CH 720P AHD + 2-CH 960H analog mixing Video input Supports 1-CH 720P/1080P IPC + 4-CH 720P AHD/960H/D1/CIF Video input Supports 1-CH 720P/1080P IPC + 4-CH 1080P AHD Video
	Video Output	1 Channels (Rear Panel on RJ45&AV-OUT Port)
	Signal System	PAL / NTSC(PAL@100 frame 1080P/sec; NTSC@120 frame 1080P/sec)
Audio	Audio Input/ Audio Output	4 Channels / 1 Channel
Recording & Storage	Video Bit Rate	960H, 720P, 1080P
Alarm	Alarm Input/ Alarm Output	4 Channels / 2 Channels
Wireless communication	3G / 4G	Supported
	Wi-Fi	Internal Wi-Fi 802.11b/g/n/ac(Optional)
GPS	Int'l Standard GPS	Internal GPS module. Real-time geographic coordinates, speed information
Operational Temperature	-25°C~80°C	Install in well ventilated area, protected from moisture, heat, dust and vibration. Confined by SSD temperature also
Weatherproof/ Water Proof	IP67	



Scan for more details

www.sharpeagle.uk